erbe

power your performance.

Bipolar instruments

Important notes

The authors and Erbe Elektromedizin GmbH have taken the greatest possible care while compiling the catalogue with electrosurgical accessories. Nevertheless, it is impossible to exclude the possibility that errors may be contained herein.

The information and recommendations given here may not be construed as constituting any basis for any claims against Erbe Elektromedizin GmbH. Should legal regulations stipulate liability, such liability shall be limited to intentional misconduct or gross negligence.

The data on the use of instruments is based on clinical experience. Medical science is subject to a process of permanent change based on research and clinical experience. Therefore the products are subject to alterations in design and technique. Because of production tolerances dimensions in the catalogue may marginally differ.

Further product information

Packaging unit _____ = 5

Notes on use _____ [i] 30191-682

4 kVp _____ Max. electrical capacity

max 95 °C _____ Temperature for cleaning in washer disinfector

max 134 °C _____ Temperature for sterilization in autoclave

② _____ Single-use product

STERILE R

STERILE R
STERILE EO _____ Sterile packaging

⊛ _____ Manual cleaning and disinfection

Please read carefully the corresponding notes on use before using any instrument.

Electrosurgery

Bipolar Instruments

Overview

Field of application	Type of instrument

Endoscopy / laparoscopy

Cutting instruments

Coagulation instruments

Bipolar instruments

LAP forceps

Bipolar LAP forceps, Maryland, deep ribbed, shaft ø 5 mm, length 340 mm

consisting of: 20195-140, 20195-141, 20195-143

		No. 20195-132
⬛ = 1		🟨 0.25 kVp
		🟥 max 95 °C
ⓘ 30195-119		🟥 max 138 °C

Bipolar LAP forceps, fenestrated, deep ribbed, shaft ø 5 mm, length 340 mm

consisting of: 20195-140, 20195-141, 20195-144

		No. 20195-133
⬛ = 1		🟨 0.25 kVp
		🟥 max 95 °C
ⓘ 30195-119		🟥 max 138 °C

Bipolar E LAP forceps, fenestrated, deep ribbed, shaft ø 5 mm, length 340 mm

consisting of: 20195-245, 20195-241, 20195-144

		No. 20195-224
⬛ = 1		🟨 0.25 kVp
		🟥 max 95 °C
ⓘ 30195-119		🟥 max 138 °C

Bipolar E LAP forceps, Maryland, deep ribbed, shaft ø 5 mm, length 340 mm

consisting of: 20195-245, 20195-241, 20195-143

		No. 20195-225
⬛ = 1		🟨 0.25 kVp
		🟥 max 95 °C
ⓘ 30195-119		🟥 max 138 °C

Bipolar instruments

LAP forceps

Single components		Piece	No.
Insert for LAP forceps, Maryland and E LAP forceps, Maryland, deep-ribbed, ø 5 mm, length 340 mm (for 20195-132 and 20195-225)		1	20195-143
Insert for LAP forceps, fenestrated and E LAP forceps, fenestrated deep-ribbed, ø 5 mm, length 340 mm (for 20195-133 and 20195-224)		1	20195-144
Shaft tube for bipolar LAP forceps and BiClamp LAP forceps, ø 5 mm, length 340 mm		1	20195-141
Shaft tube for bipolar E LAP forceps and BiClamp E LAP forceps, ø 5 mm, length 340 mm		1	20195-241
Handle for LAP forceps, without connecting cable		1	20195-140
Handle for E LAP forceps, without connecting cable		1	20195-245

Accessories for treatment		Piece	No.
Cleaning brush, length 650 mm, for manual cleaning and disinfection		1	20191-279
Rinsing tube with Luer Lock connector, length 500 mm, for cleaning and disinfection by machine		1	20195-201

Bipolar connecting cables	Connection	Length	Piece	No.
Bipolar connecting cable, VIO, ICC, ACC, T-Series, Standard	Standard Standard	4 m 5 m	1 1	20196-045 20196-057
Bipolar connecting cable, VIO, ICC, ACC, International (2-Pin 22 mm)	International International	4 m 5 m	1 1	20196-053 20196-061
Bipolar connecting cable, Martin Standard	Martin Standard Martin Standard	4 m 5 m	1 1	20196-047 20196-059
Bipolar connecting cable, Valleylab and non-Erbe units (2-Pin 28 mm)	Vallylab (2-Pin 28 mm)	4 m	1	20196-055

Bipolar instruments

LAP BiSect and bipolar LAP scissors

LAP BiSect Micro, shaft ø 5 mm, length 350 mm

consisting of: 20195-206, 20195-208, 20195-209, 20195-210

	No. 20195-204
▣ = 1	■ 0.475 kVp
	■ max 95 °C
⬛ 30195-114	■ max 138 °C

LAP BiSect Macro, shaft ø 5 mm, length 350 mm

consisting of: 20195-207, 20195-208, 20195-209, 20195-210

	No. 20195-205
▣ = 1	■ 0.475 kVp
	■ max 95 °C
⬛ 30195-114	■ max 138 °C

Single components		Piece	No.
Insert for LAP BiSect Micro (20195-204), ø 5 mm, length 350 mm		1	20195-206
Insert for LAP BiSect Macro (20195-205), ø 5 mm, length 350 mm		1	20195-207
Shaft tube for LAP BiSect Micro and Macro, ø 5 mm, length 350 mm		1	20195-208
Insulated tube for LAP BiSect Micro and Macro, ø 5 mm, length 350 mm		1	20195-209
Handle for LAP BiSect Micro and Macro		1	20195-210

Bipolar instruments

LAP BiSect and bipolar LAP scissors

Bipolar LAP scissors, Metzenbaum, shaft ø 5 mm, length 340 mm

consisting of: 20195-140, 20195-141, 20195-242

	No. 20195-226
	🟨 0.25 kVp
	🟧 max 95 °C
ⓘ 30195-119	🟥 max 138 °C

Bipolar E LAP scissors, Metzenbaum, shaft ø 5 mm, length 340 mm

consisting of: 20195-245, 20195-241, 20195-242

	No. 20195-227
	🟨 0.25 kVp
	🟧 max 95 °C
ⓘ 30195-119	🟥 max 138 °C

Single components		Piece	No.
Insert for bipolar LAP scissors Metzenbaum and bipolar E LAP scissors Metzenbaum, shaft ø 5 mm, length 340 mm (for 20195-226 and 20195-227)		1	20195-242
Shaft tube for bipolar LAP scissors, ø 5 mm, length 340 mm		1	20195-141
Shaft tube for bipolar E LAP scissors, ø 5 mm, length 340 mm		1	20195-241
Handle for LAP scissors, without connecting cable		1	20195-140
Handle for E LAP scissors, without connecting cable		1	20195-245

LAP BiSect and bipolar LAP scissors

Bipolar connecting cables	Connection	Length	Piece	No.
Bipolar connecting cable, VIO, ICC, ACC, T-Series, Standard	Standard Standard	4 m 5 m	1 1	20196-045 20196-057
Bipolar connecting cable, VIO, ICC, ACC, International (2-Pin 22 mm)	International International	4 m 5 m	1 1	20196-053 20196-061
Bipolar connecting cable, Martin Standard	Martin Standard Martin Standard	4 m 5 m	1 1	20196-047 20196-059
Bipolar connecting cable, Valleylab and non-Erbe units (2-Pin 28 mm)	Vallylab (2-Pin 28 mm)	4 m	1	20196-055

Accessories for treatment	Piece	No.
Cleaning brush, length 650 mm, for manual cleaning and disinfection	1	20191-279
Rinsing tube with Luer Lock connector, length 500 mm, for cleaning and disinfection by machine	1	20195-201

Bipolar scissors BiSect

Bipolar scissors BiSect 280, bent, length 280 mm

incl. protector 20195-195

	No. 20195-172
⬡ = 1	🟨 0.6 kVp
	🟥 max 95 °C
ℹ 30195-106	🟥 max 138 °C

Protectors for BiSect		Piece	No.
for BiSect 180		1	20195-193
for BiSect 230		1	20195-194
for BiSect 280		1	20195-195

Bipolar connecting cables	Connection	Length	Piece	No.
Bipolar connecting cable, VIO, ICC, ACC, T-Series, Standard	Standard	4 m	1	20196-106
Bipolar connecting cable, VIO, ICC, ACC, International (2-Pin 22 mm)	International	4 m	1	20196-107

Important information

The information, recommendations and other details contained in this medium ("information") reflect our state of knowledge and the state of the art in science and technology at the time the medium was created. The information is of a general nature, non-binding and intended solely for general information purposes; it does not constitute instructions for use.

The information and recommendations contained in this medium do not create any legal obligations on the part of Erbe Elektromedizin GmbH and its affiliated companies ("Erbe") or any other claims against Erbe. The information does not constitute any guarantees or other information on the nature of the product; such information requires an express contractual agreement with Erbe in each individual case.

Erbe is not liable for any kind of damage resulting from following the information on this medium, regardless of any legal grounds for liability.

Every user of an Erbe product is responsible for testing the respective Erbe product in advance with regard to its properties and its suitability for the intended type of use or purpose. Suitable type of use of the respective Erbe product can be found in the instructions for use for the respective Erbe product. The user is obliged to ascertain whether the instructions for use available to him/her correspond to the current status of the specific Erbe product. Devices may only be used in accordance with the instructions for use.

Information on settings, application sites, application duration and use of the respective Erbe product is based on the clinical experience of individual centers, physicians and clinical literature independent of Erbe as well as post market surveillance and empirical evidence. They constitute reference values, or Experienced Starting Settings, which must be checked by the user to ensure that they are suitable for the specifically planned application. Depending on the circumstances of a specific application, it may be necessary to deviate from the information provided. The user is responsible for checking this when using Erbe products. We wish to note that science and technology are subject to constant development as a result of research and clinical experience. Similarly, medicine and clinical application are constantly evolving as a result of research and technological development. This may also make it necessary for the user to deviate from the information provided on this medium.

This medium contains information about Erbe products that may not be approved/cleared in certain countries. The user of the respective Erbe product is obliged to inform himself/herself as to whether the Erbe product he/she is using is legally approved/cleared in his/her country and/or to what extent, if any, there are legal requirements for or restrictions on its use.

This medium is not intended for use in the USA.